

Seasons Greetings

from your

Kiffrost

team

Kiffrost





TRAINING PRESENTATIONS



ABC-S Plus

FULLY CERTIFIED TYPE IV AIRCRAFT DEICING/ANTI-ICING FLUID
COMPLIES WITH SAE AMS-1428

Components – CAS

Propylene Glycol – 57-55-6

Water – 7732-18-5

Other Non-Hazardous Components

CAUTION!

Avoid contact with skin and eyes. Avoid breathing mists/vapors when spraying.

PHYSICAL/HEALTH HAZARDS

Aqueous solutions may product flammable vapors. May cause eye irritation.

For Industrial Use Only
Keep out of reach of children

Kilfroost, Inc.
6250 Coral Ridge Drive, Suite 130
Coral Springs, FL 33076
Customer Service: (877) 854-5376
www.kilfroost.com

FOR CHEMICAL EMERGENCIES CALL: Chemtrec @ (800) 424-9300

Before handling or using, read and understand current Kilfroost Material Safety Data Sheet for this product.

FIRST AID

Eye contact: In case of eye contact, flush eyes immediately with fresh water for at least 15 minutes while holding eyelids open. Consult medical personnel if irritation persists.

Skin contact: Not expected to present a significant skin hazard under anticipated conditions of normal use. Wash affected area in flowing water. Remove and launder contaminated clothing before reuse.

Inhalation: Not expected to present a significant inhalation hazard under anticipated conditions of normal use. If not feeling well after exposure, move to fresh air. Consult medical personnel if symptoms persist.

Ingestion: If ingested, do not induce vomiting. Give large amounts of water to drink and consult medical personnel.

FIRE: Extinguishing media: Water, foam, carbon dioxide or dry powder.
PROPER SHIPPING NAME: Kilfroost ABC-S Plus

Type IV Aircraft De-icing/Anti-icing Fluid

PROTECTIVE EQUIPMENT

Eye: Wear eye protection if splashing is possible – chemical splash goggles and/or face shield.

Skin: If prolonged contact is likely, chemical gloves and protective coveralls are recommended.

Respiratory: Maintain sufficient ventilation to comply with "Occupational Exposure Standard." To enter a closed area where a release has occurred, wear on NIOSH/MSHA approved supplied air devices.

SPILL

Wear appropriate personal protective equipment. Contain spillage and absorb on suitable material, e.g., sawdust, sand, or earth. Transfer to a container for disposal in local landfill in accordance with local, state, or national regulations. Wash spillage area with plenty of water.

HAZARD CLASS: Not regulated.

PACKING GROUP: Not regulated.

DOT IDENTIFICATION NUMBER: Not regulated.

Net Content:

- 265 gallons
 55 gallons
 Other

Kilfroost Inc. warrants that Kilfroost ABC-S Plus Aircraft Deicer to be delivered hereunder shall conform to the specifications attached hereto, and upon receipt of payment therefore, shall be free from any security interest or encumbrance. Kilfroost, Inc. disclaims all warranties and conditions, either express or implied, including, but not limited to, implied warranties of merchantability and fitness for a particular purpose. In no event shall Kilfroost, Inc. be liable to the buyer or any third party for any indirect, incidental, special, consequential, punitive, or exemplary damages (including without limitation lost profits, lost savings, or loss of business opportunity) arising out of or relating to the deicer, or the use or inability to use the same, even if Kilfroost, Inc. has been advised of the possibility of such damages.



Rail Plus

De/Anti-Icing Fluid



For use on track, rolling stock and other rail applications



1801 Military Trail, Suite 201
 Boca Raton, Florida 33431 USA
 T 954-282-5050 www.kilfroast.com

Part of the Kilfroast Group PLC
 © 2011 Kilfroast Ltd Made in USA

55 US Gallons

Kilfroast Rail Plus

De/Anti-Icing Fluid

CONSIDERED TO BE NON-HAZARDOUS.

MAY CAUSE TEMPORARY IRRITATION TO EYES.

UNLIKELY TO IRRITATE SKIN.

CONTAINS MINIMUM 50% PROPYLENE GLYCOL.

NFPA RATINGS:
 These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA)

HEALTH HAZARD: 0

FLAMMABILITY: 1

REACTIVITY: 0

SPECIAL: NONE

FIRST AID MEASURES:

INGESTION: DO NOT INDUCE VOMITING. GIVE LARGE AMOUNTS OF WATER TO DRINK. OBTAIN MEDICAL ATTENTION.

SKIN CONTACT: WASH OFF IN FLOWING WATER. LAUNDRER CONTAMINATED CLOTHING BEFORE RE-USE.

EYE CONTACT: IRRIGATE WITH WATER FOR 15 MINUTES. OBTAIN MEDICAL ASSISTANCE IF IRRITATION PERSISTS.

INHALATION: MOVE TO FRESH AIR IF FEELING ILL. CONSULT MEDICAL PERSONNEL IF SYMPTOMS PERSIST.

HANDLING:

AVOID CONTACT WITH SKIN AND EYES.
 AVOID BREATHING MISTS/VAPORS IF SPRAYING.

STORE IN TIGHTLY SEALED ORIGINAL CONTAINERS, AWAY FROM DIRECT HEAT AND STRONG OXIDIZING AGENTS.
 DO NOT REUSE CONTAINER.

Kilfroast, Inc. 1801 North Military Trail, Suite 201 Boca Raton, Florida 33431 USA
 Tel: 954-282-5050 Fax: 800-483-2578 kilfroast.com

Kilfrost

ABC-S Plus Type IV



Aircraft De-icing and Anti-icing Fluid



1801 Military Trail, Suite 201
Boca Raton, Florida 33431 USA
T 954-282-5050 www.kilfrost.com

Part of the Kilfrost Group PLC

© 2011 Kilfrost Ltd Made in USA

270 US Gallons

WARNING:

HARMFUL OR FATAL IF SWALLOWED;
READ CAREFULLY OTHER WARNINGS AND CAUTIONS
ON THE BACK PANEL

TKS 406B

in flight ice protection

2.5 US Gallons

experience **quality** reliability

AEROSPACE

